



Mobile Computer



Android



4G



Wi-Fi



Bluetooth



1D Barcode



2D Barcode



Fingerprint



PSAM



UHF



Infrared



NFC/HF



Camera



GPS

This device with abundant functions is an Android rugged mobile computer. With its powerful processor, stable wireless connections and comprehensive data capture options, you can find this easy-to-deploy device a valuable helper to increase productivity in logistics, warehousing, retail, identity verification, meter reading, IC card reading and etc.



Specification

Performance	
CPU	Octa-core, 2.3GHz
RAM+ROM	3GB + 32GB / 4GB + 64GB (optional)
Expansion	Supports up to 256GB Micro SD (TF) card
Operating System	Android 11 / 13; GMS, FOTA, Soti MobiControl, SafeUEM supported.

Communication	
WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
WWAN	2G: GSM850/GSM900/DCS1800/PCS1900
	3G: WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA: A/F
	4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/ B34/B38/B39/B40/B41
Bluetooth	Bluetooth 5.0
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Physical Characteristics	
Dimensions	164.2 x 78.8 x 17.0 mm / 6.46 x 3.1 x 0.67 in. (for standard version)
Weight	<288 g / 10.15 oz. (for standard version)
Display	5.2" IPS LTPS 1920x1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, built-in 5000 mAh
	Standby: over 350 hours
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB 2.0 Type-C, OTG, TypeC headphones supported
Sensors	Light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key

Developing Environment	
SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment	
Operating Temp.	-4 °F to 122 °F / -20 °C to 50 °C
Storage Temp.	-40 °F to 158 °F / -40 °C to 70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.8 m / 5.9 ft. drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP65 / IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±6 KV conductive discharge

* Operating temperature of UHF version: -20°C to 45°C

Data Collection	
Camera	
Rear Camera	13 MP Autofocus with flash
Front Camera (optional)	5 MP camera

Barcode Scanning (optional)	
1D Linear Scanner	Honeywell: N4313
1D Symbolgies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603; CM60
2D Symbolgies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

HF (optional)	
Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693
Chips	M1 card (S50/S70), M0 (Ultralight), M3 (Desfire D40/D41/D81), CPU_A card, CPU_B card, ICODE II, TI2048, LRI64K, Others for customization
Range	3-8 cm

NFC	
Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

UHF (optional)	
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
* For detailed specification, please check C71 UHF data sheet	

InfraRed (optional)	
Frequency	38 kHz
* For detailed specification, please check C71 InfraRed data sheet	

Fingerprint (optional)	
Sensor	Capacitive TCS1 / TLK1NC02; Optical Morpho CBM-E3
* For detailed specification, please check C71 Fingerprint data sheet	

PSAM (optional)	
Card slot	2 slots for PSAM cards
Protocol	ISO7816 T=0, T=1

Accessories	
Standard	AC Adaptor, USB Cable, Lanyard, etc.
Optional	Cradle, Holster, etc.
* For detailed specification, please check Accessory Guide.	

--