



# Fixed UHF Reader

This is a high-performance four-channel fixed UHF reader. The core chip adopts Impinj E710 module with high integration and excellent performance. With Stable and reliable capacity, excellent anti-electromagnetic interference capability and heat dissipation performance, it meets the requirements for installation and application of various indoor and outdoor environments and can be applied in multiple industries with strict RFID application standard such as warehouse management, archives and library management, bank, clothing and footwear retail, jewelry monitoring, watch industry, laundry, production line management, medical instrument cabinet and vending machines.



# Specification

Physical Characteristics	
Dimensions	102.8 mm(L) x 102.8 mm(W) x 28 mm(H)
Weight	329 g / 11.6 oz. (without antenna)
Material	Aluminium alloy
Input Voltage	DC 9V – 12V
Standby Current	< 30mA
Work Current	800mA +/-5% @ DC 12V Input
Comm Interface	RS-232 / RJ45
GPIO	2 channel input optical coupling, 1 channel output electric relay, 1 channel output optical coupling (in reserve)
Baud Rate	115200 bps
Cooling Mode	Air cooling
Ethernet interface	10/100 Base-T Ethernet (RJ45)
Power	POE (802.3af 13W) (Optional) POE+ (802.3at 25.5W) (Optional)
User Environment	
Operating Temp.	-13°F to 149°F / -25 °C to 65 °C
Storage Temp.	-40°F to 185°F / -40 °C to 85 °C
Humidity	10%- 95%
Developing Environment	

SDK	Windows, Linux, Android
UHF	
Engine	Based on Impinj E710
Protocol	EPC global UHF Class 1 Gen 2 / ISO 18000-6C
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Output Power	1W (30dBm, support +5~+30dBm adjustable) 2W Optional (33dBm, support +10~+33dBm adjustable, for Latin America, etc.)
Output Power Precision	+/- 1dB
Output Power Flatness	+/- 0.2dB
Receive Sensitivity	< -84dBm
Fastest Read Rate	900+ tags/sec
RSSI	Supported
Ambient Temp Monitor	Supported
Antenna Detector	Supported
Antenna	Supporting a variety of antennas, such as 6dBic, 9dBic
Antenna Port	4 channel 50Ω SMA port